







# Stabilizer bar with integral end links for a vehicle suspension system

**Patent number:** EP1153775  
**Publication date:** 2001-11-14  
**Inventor:** KEENEY CHRIS (US); YOLICK STEVE (US); CLEMENTS MARK (US); FADER JOE (US); HAWKINS JIM (US)  
**Applicant:** MERITOR LIGHT VEHICLE SYS LTD (US)  
**Classification:**  
- international: **B21K1/02; B21K1/44; B60G7/00; B60G21/055; F16C11/06; B21K1/00; B60G7/00; B60G21/00; F16C11/06; (IPC1-7): B60G21/055; B21K1/44; B60G7/00; F16C11/06**  
- european: **B21K1/02; B21K1/44; B60G7/00B; B60G21/055B; F16C11/06C2**  
**Application number:** EP20010304093 20010504  
**Priority number(s):** US20000567457 20000508

**Also published as:**

 US6648350 (B1)


**Cited documents:**

 WO9819873  
 US5954353  
 US3033587  
 DE4443809  
 GB1387650  
more >>

[Report a data error here](#)

## Abstract of EP1153775

A suspension system includes a stabilizer bar having an integral ball link directly formed as each end of the stabilizer bar. Because the ball link is integral to the stabilizer bar, there are no bolts, nuts or other fasteners that limit the articulation of the end link relative to the stabilizer bar. The present invention thereby provides greater end link articulation and improved suspension system performance.



Data supplied from the [esp@cenet](mailto:esp@cenet) database - Worldwide

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 1 153 775 A1**

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
14.11.2001 Bulletin 2001/46

(51) Int Cl.7: **B60G 21/055**, B60G 7/00,  
F16C 11/06, B21K 1/44

(21) Application number: 01304093.6

(22) Date of filing: 04.05.2001

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

- Yollick, Steve  
Troy, Michigan 48098 (US)
- Clements, Mark  
Lapeer, Michigan 48446 (US)
- Fader, Joe  
Brighton, Michigan 48114 (US)
- Hawkins, Jim  
Madison, Alabama 35758 (US)

(30) Priority: 08.05.2000 US 567457

(71) Applicant: Meritor Light Vehicle Systems, Inc.  
Troy, Michigan 48084 (US)

(74) Representative: Jones, John Bryn et al  
Withers & Rogers,  
Goldings House,  
2 Hays Lane  
London SE1 2HW (GB)


(72) Inventors:

- Keeney, Chris  
Troy, Michigan 48083 (US)

### (54) Stabilizer bar with integral end links for a vehicle suspension system

(57) A suspension system includes a stabilizer bar having an integral ball link directly formed as each end of the stabilizer bar. Because the ball link is integral to the stabilizer bar, there are no bolts, nuts or other fas-

teners that limit the articulation of the end link relative to the stabilizer bar. The present invention thereby provides greater end link articulation and improved suspension system performance.



## Description

**[0001]** The present invention relates to a suspension system for a vehicle, and more specifically to a stabilizer bar having an integral ball link.

**[0002]** Vehicles are commonly equipped with independent suspension systems for absorbing road shock and other vibrations while providing a smooth and comfortable ride for the vehicle occupants. In suspension systems of this type, a stabilizer bar is often used to increase the roll rigidity and improve the steering stability of the vehicle.

**[0003]** Typically, the stabilizer bar is a rod-shaped member oriented to extend laterally across the vehicle and an arm segment extending longitudinally at each end of the central segment. The central segment of the stabilizer bar is supported for rotation about its own longitudinal axis by one or more mounting brackets which are fixed to the vehicle body or frame. The distal end of each arm segment is coupled to a control arm of the suspension system by an end link.

**[0004]** When the vehicle is subjected to a lateral rolling force such as, for example, while the vehicle negotiates a turn, the arm segments pivot in opposite directions with respect to the longitudinal axis of the central segment. As a result, torsional reaction forces are generated which act through the arm segments to urge the control arms to move toward their normal position. Thus, the vehicle body will be prevented from excessive rolling or leaning to either side by the torsional resistance produced by the stabilizer bar.

**[0005]** As noted, each end of the stabilizer bar is typically attached to a corresponding control arm by an end link. One type of known stabilizer bar end link includes a connector at each end extending at right angles to the longitudinal axis of the link itself. The connectors attach to corresponding ball studs on the stabilizer bar and a vehicle frame component. Ball studs are preferred as they permit a rather large area of movement.

**[0006]** The area of movement provided by the ball link is definable as a conical area. The ball studs are commonly manufactured as one-piece units which are attached to the stabilizer bar and vehicle frame by a fastener such as a bolt. However, these fasteners can interfere with movement of the connectors and reduce end link articulation thereby reducing the conical area. Disadvantageously, this reduced end link articulation limits the overall suspension system articulation. Further, because the ball studs are typically manufactured independently and are fastened to the stabilizer bar, multiple machine operations are necessary and substantial weight is added to the suspension system.

**[0007]** The suspension system according to the present invention provides a stabilizer bar having an integral ball link directly formed as each end of the stabilizer bar. Because the ball link is integral to the stabilizer bar, there are no bolts, nuts or other fasteners that limit the articulation of the end link relative to the stabilizer

bar. The present invention thereby provides greater end link articulation and improved suspension system performance.

**[0008]** The various features and advantages of this invention will become apparent to those skilled in the art from the following detailed description of the currently preferred embodiment. The drawings that accompany the detailed description can be briefly described as follows:

Figure 1 is a general phantom view of a vehicle illustrating a suspension system;

Figure 2 is an expanded view of a stabilizer bar having an integral ball link according to the present invention;

Figure 3A is an expanded view of the stabilizer bar of Figure 2 attached to an end link; and

Figure 3B shows one feature of the Figure 3A construction.

**[0009]** Figure 1 illustrates a schematic perspective view of a vehicle suspension system 10. In the disclosed embodiment, a double transverse link suspension system is illustrated wherein two vehicle wheels 12, are each articulatably connected to a vehicle chassis (schematically indicated at 14) by transverse links 16. A stabilizer bar 18 is movably supported at a mounting bracket 20 from the vehicle chassis 14 in a conventional manner. The stabilizer bar 18 includes two arms 22 extending substantially lengthwise of the vehicle. The arms 22 are articulatably joined to the lower transverse link 16 on each side by an end link 24.

**[0010]** Referring to Figure 2, a top view of the stabilizer bar 18 according to the present invention is illustrated. The stabilizer bar 18 includes a ball link 26 directly formed as each end 28 of the stabilizer bar 18. The stabilizer bar 18 is supported by a mounting bracket 20 to the vehicle chassis 14. Although, only one half of the stabilizer bar is illustrated, it should be understood that both ends of the stabilizer bar include the ball link 26. The ball link 26 is preferably manufactured integral to the stabilizer bar by such methods as machining, rotary swaging, rotary forming or the like. The ball link 26 may also be separately manufactured and attached to the stabilizer bar 18 by friction welding, complimentary threads, or the like. Stated another way, the area 29 inward of ball is of a smaller outer diameter than the ball 26 throughout the length of bar 18 which could interfere with its mounting structure.

**[0011]** Figure 3A, illustrates the stabilizer bar 18 attached to the end link 24 by a connector 30. Because the ball link 26 is integral to the stabilizer bar 18, an inner area 29 is formed. The inner area 29 is devoid of bolts, nuts or other fasteners that would otherwise interfere

with connector 30 and limit articulation of the end link 24 relative to the stabilizer bar 18.

[0012] As shown in Figure 3B, the bar 18 and ball 26 are movable within connector 30. The inner area 29 is smaller than ball 26 such that the bar 18 can move freely within connector 30. It should be understood that inner area 29 can have a diameter greater or less than said stabilizer bar 18, as long as it does not interfere with articulation of the connector 30 and ball 26. The present invention thereby provides greater end link 24 articulation and improved suspension system performance.

[0013] The foregoing description is exemplary rather than defined by the limitations within. Many modifications and variations of the present invention are possible in light of the above teachings. The preferred embodiments of this invention have been disclosed, however, one of ordinary skill in the art would recognize that certain modifications would come within the scope of this invention. It is, therefore, to be understood that within the scope of the appended claims, the invention may be practiced otherwise than as specifically described. For that reason the following claims should be studied to determine the true scope and content of this invention.

## Claims

1. A suspension system for a vehicle (10) comprising: a suspension member (16); an end link (24) attachable to said suspension member, said end link having a ball socket (30); and a stabiliser bar (18) having a ball link (26) fittable into said ball socket, said ball link being integrally formed as an end of said stabiliser bar, said stabiliser bar defining an inner area (29) adjacent said ball link for unobstructed articulation of said ball socket.
2. The suspension system as recited in Claim 1, wherein said inner area is devoid of fasteners between said ball link and said stabiliser bar.
3. The suspension system as recited in Claim 1 or Claim 2, wherein said ball link is machined on to said end stabiliser bar.
4. The suspension system as recited in Claim 1 or Claim 2, wherein said ball link is rotary swaged on to said end of said stabiliser bar.
5. The suspension system as recited in Claim 1 or Claim 2, wherein said ball link is rotary formed on to said end of said stabiliser bar.
6. A method of increasing articulation of a vehicle suspension system (10) having a stabiliser bar (18) and an end link (24) comprising the steps of:
  - (i) integrally forming an inner area between an end of said stabiliser bar and a male link; and
  - (ii) fitting said male link into a female socket attached to an end link such that said end link is articulatable within said inner area.
7. A method as recited in Claim 6, wherein said step (i) includes forming said male link as a ball link (26).

Fig 1




Fig 2




Fig 3b





Fig 3A





European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 30 4093

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 98 19873 A (MUHR & BENDER ; MUHR THOMAS (DE); SCHARIOTH RUEDIGER (DE)) 14 May 1998 (1998-05-14)	1,6,7	B60G21/055 B60G7/00 F16C11/06 B21K1/44
Y	* the whole document *	2-5	
X	US 5 954 353 A (KINCAID JEFFREY L ET AL) 21 September 1999 (1999-09-21)	1,6,7	
Y	* abstract; figures 1-3 *	2-5	
Y	US 3 033 587 A (PERISH, P.W.) 8 May 1962 (1962-05-08) * column 4, line 9 - line 24; figures 4,5 *	1-3,5-7	
Y	DE 44 43 809 A (FICHEL & SACHS AG) 4 April 1996 (1996-04-04) * figures 1,3 *	1-3,5	
Y	PATENT ABSTRACTS OF JAPAN vol. 013, no. 465 (M-882), 20 October 1989 (1989-10-20) & JP 01 182109 A (NHK SPRING CO LTD), 20 July 1989 (1989-07-20) * abstract; figures 1,6,10 *	1-7	
Y	PATENT ABSTRACTS OF JAPAN vol. 013, no. 258 (M-838), 15 June 1989 (1989-06-15) & JP 01 062243 A (SANWA KINZOKU KOGYO KK), 8 March 1989 (1989-03-08) * abstract; figures 1,2 *	3	TECHNICAL FIELDS SEARCHED (Int.Cl.7) B60G B21K F16C B62D
Y	GB 1 387 650 A (PERRIER J) 19 March 1975 (1975-03-19) * page 1, line 24 - line 38; figures *	5	
		-/--	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 August 2001	Examiner Tsitsilonis, L
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 30 4093

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	PATENT ABSTRACTS OF JAPAN vol. 1997, no. 11, 28 November 1997 (1997-11-28) & JP 09 177762 A (RHYTHM CORP), 11 July 1997 (1997-07-11) * abstract *	4, 5	
A	US 3 740 986 A (SCHMID L) 26 June 1973 (1973-06-26) * abstract; figures 1-3, 12-16 *	1, 2, 5-7	
A	PATENT ABSTRACTS OF JAPAN vol. 018, no. 289 (M-1614), 2 June 1994 (1994-06-02) & JP 06 055237 A (RHYTHM CORP), 1 March 1994 (1994-03-01) * abstract *	4, 5	
A	PATENT ABSTRACTS OF JAPAN vol. 012, no. 294 (M-730), 11 August 1988 (1988-08-11) & JP 63 072447 A (MUSASHI SEIMITSU IND CO LTD; OTHERS: 02), 2 April 1988 (1988-04-02) * abstract; figures *	4	
A	EP 0 775 603 A (TRW FAHRWERKSYST GMBH & CO) 28 May 1997 (1997-05-28)		
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>16 August 2001</b>	Examiner <b>Tsitsilonis, L</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 4093

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-08-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9819873 A	14-05-1998	DE 19645132 A AU 6089998 A	07-05-1998 29-05-1998
US 5954353 A	21-09-1999	BR 9900766 A DE 19903562 A US 6007080 A	21-12-1999 12-08-1999 28-12-1999
US 3033587 A	08-05-1962	NONE	
DE 4443809 A	04-04-1996	NONE	
JP 01182109 A	20-07-1989	NONE	
JP 01062243 A	08-03-1989	NONE	
GB 1387650 A	19-03-1975	FR 2187457 A DE 2261154 A ES 410410 A IT 976048 B	18-01-1974 20-12-1973 01-05-1976 20-08-1974
JP 09177762 A	11-07-1997	DE 19645410 A KR 190601 B US 6038771 A	26-06-1997 01-06-1999 21-03-2000
US 3740986 A	26-06-1973	DE 1900642 A DE 1916451 A DE 1916832 A DE 1916833 A ES 179768 Y FR 2027951 A GB 1263682 A US 3594026 A	13-08-1970 08-10-1970 05-11-1970 15-10-1970 16-12-1973 02-10-1970 16-02-1972 20-07-1971
JP 06055237 A	01-03-1994	DE 4319076 A	09-12-1993
JP 63072447 A	02-04-1988	NONE	
EP 0775603 A	28-05-1997	DE 19543690 A DE 59606307 D JP 9175139 A US 5876148 A	28-05-1997 15-02-2001 08-07-1997 02-03-1999